

ENTRYPASS QR CODE SERIES

Entrypass QR Code Reader and Module



Picture shown is for illustration purposes only. Actual products may vary due to product enhancement.

Entrypass QR series consists of QR code reader and module that enables transformation of user experience in the access control and visitor management environment with more convenience, speed and security.



Available with different technologies,
QR code, Mifare & DesFire.



Tamper protection



Economical mounts type



Support on-site Reader Configuration Card
to change certain parameters



Easily seen under dark environment
with back lit design



www.entypass.net

ENTRYPASS QR CODE SERIES

Entrypass QR Code Reader and Module



Picture shown is for illustration purposes only. Actual products may vary due to product enhancement.

User Friendly Installation



All weatherproof design with IP65 certificate.




All inputs are 12V DC protected.



Universal back plate allows the reader to be installed in different size of gang box.



Non-drop bottom screw made servicing handier.



Metal back plate allows the reader to be installed on metal surface back to back without affecting the read range.



Reverse power protection.



All input and output signals are protected against static charges.



Stainless steel security screw.

ENTRYPASS QR CODE SERIES

Entrypass QR Code Reader and Module

Technical Specifications

Model	EP.QR3001M EP.QR3001M.WIE	EP.QR3002R EP.QR3002R.WIE	EP.QR3003MDBR EP.QR3003MDBR.WIE
Dimension	88mm*75mm*17.5mm	115.5mm*84.5mm*20.5mm	
Weight	50g	210g	
Communication Interface RS-485 (OSDP) <small>*Read only Entrypass QRCode through secured channel</small>	EP.QR3001M	EP.QR3002R	EP.QR3003MDBR
Baud Rate	9600 (Default)		
BLE Ready	N/A	Yes	Yes
Reading Technologies	QR code only	QR Code and BLE	QR Code, BLE , Card Supported (Mifare & DesFire EV1 & EV2)
Read Range	QR: 4-18cm		QR: 4-18cm RFID (13.56MHz): 1-8cm
Card Format	-		Wiegand 26, 34 & other formats (configurable)
Card Technology	-		ISO 14443A CSN Mifare CSN / Sector DesFire (EV1, EV2) CSN / Content
Input Voltage	12/24 VDC		
Operating Current	250mA (max)		
IP Rating	IP65		

Ordering Information:

EP.QR3001M	Entrypass QR Reader Module
EP.QR3001M.WIE	Entrypass QR Reader Module with wiegand protocol
EP.QR3002R	Entrypass QR Reader
EP.QR3002R.WIE	Entrypass QR Reader with wiegand protocol
EP.QR3003MDBR	Entrypass QR Reader that support Mifare classic, Desfire EV1/EV2 & Bluetooth enabled
EP.QR3003MDBR.WIE	Entrypass QR Reader that support Mifare classic, Desfire EV1/EV2 & Bluetooth enabled with wiegand protocol



www.entypass.net

Malaysia

No. 40, Jalan TPP 1/10, Taman Industri Puchong, Batu 12 Jalan Puchong, 47160 Puchong Selangor Darul Ehsan, Malaysia.
Tel : +603 8068 1929
Fax : +603 8062 6937
Email : info@entypass.net

Singapore

No. 1, UBI View, #03-03, Focus ONE Building, Singapore 408555.
Tel : +65- 6841 7242
Fax : +65- 6841 3937
Email : info@entypass.net

Indonesia

Rukan Puri Mutiara, Block BF No.17, Jln Griya Utama, Sunter Agung, Jakarta Utara, 14350, Indonesia.
Tel : +62 21 2937 6098
Email : indonesia@entypass.net