

EP.FR2010M


Entrypass Facial Recognition Terminal

Features

- 7-inch LCD touch screen
- 2 Mega pixel wide angle-lens
- Recognition distance: 0.3 to 3 m
- Face recognition duration < 0.2 s/ User
- Face recognition accuracy rate $\geq 99\%$
- Built-in Mifare card and DesFire card reading module (Presents card on the screen to authenticate)
- 10,000 face capacity, 50,000 card capacity and 150,000 event capacity
- Face mask detection
- Supports ISAPI, ISUP 5.0, TCP/IP (IPv4 and IPv6)
- Support single person and multiple people (Up to 5 people) recognition
- Stand-alone operation



No.	Description
①	MIC
②	IR Light
③	Type-C USB Interface
④	IR Light
⑤	Camera
⑥	Breathing Light
⑦	Loudspeaker
⑧	Wiring Terminal
⑨	Temperature Module Interface
⑩	Debugging Port (For debugging only)
⑪	Network Interface
⑫	Audio Output
⑬	Tamper
⑭	SIM Card Slot
⑮	TF Card Slot (Reserved)



Peripheral Module

EP.FR2010M

Entrypass Facial Recognition Terminal



Technical Specification

Operation system	Linux
Screen	7 Inch, Touch Screen
FOV	HFOV= 75.5 ; VFOV=41.5 ; DFOV=87
Pixel	2MP
Lens	DUAL-Lens
Video standard	PAL (Default)/NTSC
Wired Network	Support 10/100/1000 Mbps self-adaptive
Wi-Fi	Support
Alarm Input	1
Alarm Output	1
USB	1 (For Module)
Audio Output Interface	1 (3.5mm)
Network interface	1
RS- 485	1
Wiegand	1
Lock output	1
Exit button	1

EP.FR2010M

Entrypass Facial Recognition Terminal



Technical Specification

Door contact input	1
TAMPER	1
Card capacity	50,000
Face capacity	10,000
Event capacity	150,000
Face recognition accuracy rate	≥ 99%
Card type	Mifare card / DesFire card
Card reading distance	0 to 3 cm
Card reading duration	< 1 s
Face recognition distance	0.3 to 3 m
Face recognition duration	< 0.2 s per person
Two-way audio	Support
Time synchronization	Support
Face anti spoofing	Support
Live view	Support
Audio prompt	Support
Power Supply	12 VDC to 24 VDC/2 A
Working temperature	- 30 c to 60 c (- 22 F to 140 F)
Working humidity	0 to 90% (no condensing)
Protective level	IP65
Dimensions	110.5mm x 209.2mm x 24mm (4.35" x 8.24" x 0.94")
Weight	Gross weight: 1.06 kg (2.34 lb), Net weight: 0.57 kg (1.26 lb)
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese Portuguese (Brazil), Japanese, Korean

EP.FR2010M

Entrypass Facial Recognition Terminal

Dimension



Peripheral Module

Ordering Information

EP.FR2010M

Entrypass Facial Recognition Terminal. Support 10,000 Facial Template Capacity and MIFARE Reader.



www.entrypass.net

Malaysia

No. 40, Jalan TPP 1/10, Taman Industri Puchong,
Batu 12 Jalan Puchong, 47160 Puchong
Selangor Darul Ehsan, Malaysia.
Tel : +603 8068 1929
Fax : +603 8062 6937
Email : info@entrypass.net

Singapore

No. 1, UBI View, #03-03, Focus ONE Building,
Singapore 408555.
Tel : +65- 6841 7242
Fax : +65- 6841 3937
Email : info@entrypass.net

Indonesia

PT Brikom Entripas Indonesia
Jl. Griya Utama, Komplek Puri Mutiara Blok BF No. 17,
RT.1/RW.20, Sunter Agung, Tj. Priok, Kota Jkt Utara,
Daerah Khusus Ibukota Jakarta 14350.
Tel : +62 21 2937 6098
Email : info@entrypass.net